

## ELECTRIC SCISSOR LIFTS

# 0407SE (1530SE)

Compliant with CE/AS/CSA/AS/EAC/KCS standards

### PRODUCT HIGHLIGHTS

- Easily passes through standard doors and can access elevators
- The short design of sliding rail makes debris easy to clean
- Bumper rail and indented sliding rail designed for anti-scratch
- DC motor drive, giving a longer runtime



Standard Features		
2WD×2WS	Maintenance-free battery	Fault diagnosis system
Non-marking tires	Proportional control	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Flashing beacon	Forklift pockets and lifting points	Overload sensing system
Foldable guardrail	Automatic pothole protection	Manual storage box
Drivable at full height	Bumper rails	Auto braking system
White noise Alarm	Trackunit-ready connector	
Options & Accessories		
RCBO	Battery isolater	
AC power to platform	EQSS/Protector	

**SINOBOOM™**

**PARTNERS IN ACCESS™**

SINOBOOM.COM | SALES@SINOBOOM.COM  
32-34 Marni Street, Dandenong South, VIC Australia 3175

# ELECTRIC SCISSOR LIFTS

## 0407SE (1530SE)

Compliant with CE/ANSI/CSA/AS/EAC/KCS standards

Model	0407SE (1530SE)
<b>Dimensions</b>	
Max Working Height(Indoor/Outdoor)	6.5 m/5.8 m (21'3.9"/19')
A Max Platform Height(Indoor/Outdoor)	4.5 m/3.8 m (14'9.2"/12'5.6")
B Platform Extension	0.6 m (2')
C Length-Stowed	1.42 m (4'7.9")
D Width-Stowed	0.76 m (2'5.9")
E Height-Stowed (Rails Folded)	1.67 m (5'5.8")
E Height-Stowed (Rails Unfolded)	1.97 m (6'5.6")
F Wheelbase	1.11 m (3'7.7")
Ground Clearance (Pothole Guard Stowed)	0.061 m (2.4")
Ground Clearance (Pothole Guard Deployed)	0.02 m (0.75")
Platform Size (L×W×H)	1.34 m×0.7 m×1.1 m (4'4.8"×2'3.6"×3'7")
<b>Performance</b>	
Platform Capacity	240 kg (529 lbs)
Extension Platform Capacity	115 kg (254 lbs)
Max Platform Occupants (Indoor/Outdoor)	2 Persons (Indoor) 1 Person (Outdoor)
Drive Speed (Stowed)	0~4 km/h (0~2.5 mph)
Drive Speed (Raised)	0~0.8 km/h (0~0.5 mph)
Lift Time (Unloaded)	20s~23s
Lower Time (Unloaded)	25s~27s
Gradeability	25%
Max Allowable Inclination (front-to-back/side-to-side)	3°/1.5°
Turning Radius (Inside/Outside)	0.3 m/1.35 m (12'/4'5")
Tire Size/Type	255×76 mm (10×3") /solid
<b>Power</b>	
Drive×Steer	2 WD×2 WS
Power Source (V/kW)	24 V/2.2 kW
Drive Motor (V/kW)	24 V DC/0.4 kW
Hydraulic Tank Capacity	4 L (0.9 gal (UK)/1.05 gal(US))
Batteries	24 V,120 Ah (Lead acid battery)
Charger (Input/Output)	100~240 V AC/15 A
<b>Weight</b>	
Weight (Indoor/Outdoor)	880 kg (1,941 lbs)
Standards Compliance	CE/ANSI/CSA/AS/EAC/KCS

